METRIC DIGITAL OUTSIDE MICROMETER

- Resolution 0.001mm
- IP54 dust/waterproof
- Button function: on/off, set, ABS/INC
- No data output
- LR44 battery, automatic power off
- Carbide measuring faces
- Supplied with spherical anvil
- Setting standards are included (except 0-25mm)




(mm)





3108-25A







(mm)

Ratchet stop type

ivarcinet stop i				(''''' <i>'</i>		
Code	Range	Accuracy	L	а	b	С
3108-25A*	0-25mm	±2µm	32.5	6	24	3
3108-50A*	25-50mm	±2µm	57.5	8	32	3
3108-75A*	50-75mm	±3µm	82.5	8	44.5	3
3108-100A*	75-100mm	±3µm	107.5	8	57	3
3108-125A	100-125mm	±3µm	133	10	70	3
3108-150A	125-150mm	±3µm	158.5	10	82	3
3108-175A	150-175mm	±4µm	184	12	94.5	5.5
3108-200A	175-200mm	±4µm	209.5	12	107	5.5



spherical anvil

measure tube

wall thickness

Code Range Accuracy L a b c 3108-25FA* 0-25mm ±2µm 32.5 6 24 3	3.							
3108-25FA* 0-25mm ±2μm 32.5 6 24 3								
	3108-25FA*	0-25mm	±2µm	32.5	6	24	3	

^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany